

# DEFY 2

LIGHT AND LIVELY. THAT'S HOW TEST EDITORS OFTEN DESCRIBE THE AWARD-WINNING DEFY. FIND OUT FOR YOURSELF WHY THE EXPERTS ARE RIGHT.



## SPECIFICATIONS

|            |                  |                                                               |                               |
|------------|------------------|---------------------------------------------------------------|-------------------------------|
| FRAME      | SIZES            | XS,S,M,M/L,L,XL                                               |                               |
|            | COLORS           | White/Black/Yellow                                            |                               |
|            | FRAME            | ALUXX SL-Grade Aluminum                                       |                               |
|            | FORK             | Advanced-Grade Composite, Alloy<br>OverDrive Steerer          |                               |
|            | SHOCK            | N / A                                                         |                               |
|            | COMPONENTS       | HANDLEBAR                                                     | Giant Connect, 31.8           |
|            |                  | STEM                                                          | Giant Connect                 |
|            |                  | SEATPOST                                                      | Giant Connect Composite, 30.9 |
|            |                  | SADDLE                                                        | Giant Performance Road, Men's |
|            |                  | PEDALS                                                        | Caged w/ Clips                |
| DRIVETRAIN | SHIFTERS         | Shimano Tiagra                                                |                               |
|            | FRONT DERAILLEUR | Shimano Tiagra                                                |                               |
|            | REAR DERAILLEUR  | Shimano Tiagra                                                |                               |
|            | BRAKES           | Tektro TK-R340 Giant Specific, Dual<br>Pivot                  |                               |
|            | BRAKE LEVERS     | Shimano Tiagra                                                |                               |
|            | CASSETTES        | Shimano HG50 12x25, 9-speed                                   |                               |
|            | CHAIN            | Shimano HG-73                                                 |                               |
|            | CRANKSET         | Shimano Tiagra, 34/50                                         |                               |
|            | BOTTOM BRACKET   | Shimano, External                                             |                               |
|            | WHEELS           | RIMS                                                          | Giant S-R2                    |
| HUBS       |                  | [F] Formula Sealed, [R] Shimano 2200,<br>32h                  |                               |
| SPOKES     |                  | Stainless Steel, 14g                                          |                               |
| TIRES      |                  | Giant P-R3, 60 tpi, Flat Guard, [F] & [R]<br>specific, 700x25 |                               |
| EXTRAS     |                  |                                                               |                               |

## FRAME TECHNOLOGY

Pure performance from the world's most advanced aluminum engineers. With its lightweight, stiff, ride-tuned ALUXX SL frameset, Defy breaks all the rules of what was previously thought possible for an entry-level road bike. Fitted with performance wheels and parts, it climbs, corners and sprints like bikes costing thousands more.



### KEY UPGRADES (OVER DEFY 3)

- Full 9-speed Shimano Tiagra shifting
- Giant Connect (composite) seatpost
- Flat-resistant Giant P-R3 tires

## FRAME GEOMETRY

| Actual Frame Size | Part Number | Head Angle | Seat Angle* | Toptube**   | Headtube    | Chainstay   | Wheelbase   | Standover Height*** |
|-------------------|-------------|------------|-------------|-------------|-------------|-------------|-------------|---------------------|
| Centimeters       |             | Degrees    | Degrees     | Centimeters | Centimeters | Centimeters | Centimeters | Inches              |
| XS/43.0           | 383172      | 71.0       | 74.0        | 51.5        | 12.5        | 42.0        | 98.3        | 29.0                |
| S/46.5            | 383173      | 72.0       | 74.0        | 53.0        | 14.5        | 42.0        | 99.0        | 29.7                |
| M/50.0            | 383174      | 72.5       | 73.0        | 54.5        | 16.5        | 42.0        | 99.0        | 30.6                |
| M/L/53.5          | 383175      | 72.5       | 73.0        | 56.0        | 18.5        | 42.0        | 100.5       | 31.1                |
| L/55.5            | 383176      | 72.5       | 72.0        | 57.5        | 20.5        | 42.0        | 100.8       | 32.0                |
| XL/58.5           | 383177      | 72.5       | 72.0        | 59.5        | 22.5        | 42.0        | 102.8       | 32.8                |

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire