

DEFY ADVANCED 0

THE MORE COMFORTABLE YOU ARE, THE MORE YOU'LL RIDE. THE MORE YOU RIDE, THE FASTER YOU GET. ENDURANCE AND SPEED, A WINNING COMBO.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,ML,L,XL	
	COLORS	Composite/White/Blue	
	FRAME	Advanced-Grade Composite	
COMPONENTS	FORK	Advanced-Grade Composite, Full Composite OverDrive Steerer	
	SHOCK	N / A	
	HANDLEBAR	Giant Contact SLR, Composite, 31.8	
	STEM	Giant Contact SLR, Composite	
	SEATPOST	Giant Vector Composite	
	SADDLE	Fi'zi:k Antares w/ Braided Composite Rails	
	PEDALS	Not Included	
	DRIVETRAIN	SHIFTERS	Shimano Dura-Ace 7900
		FRONT DERAILLEUR	Shimano Dura-Ace 7900
		REAR DERAILLEUR	Shimano Dura-Ace 7900
BRAKES		Shimano Dura-Ace 7900	
BRAKE LEVERS		Shimano Dura-Ace 7900	
WHEELS	CASSETTES	Shimano Dura-Ace 7900 11x28, 10-speed	
	CHAIN	Shimano Dura-Ace 7900	
	CRANKSET	Shimano Dura-Ace 7900, 34/50	
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit	
	RIMS	Shimano Dura-Ace Carbon WH-7850-C24-TL	
	HUBS	Shimano Dura-Ace	
	SPOKES	Shimano Dura-Ace	
	TIRES	Michelin Pro Optimum, 700x25 Folding, [F] & [R] specific	
EXTRAS			

Specifications and availability subject to change without notice

FRAME TECHNOLOGY

At the heart of this aero-sculpted beauty is an Advanced-grade composite frame with endurance-geometry for increased control and comfort. Performance features like the PowerCore bottom bracket for optimal pedaling stiffness are blended with road-smoothing features including a longer wheelbase and taller head tube. It's the best of both worlds.



KEY UPGRADES (OVER DEFY ADVANCED 1)

- Complete 10-speed Shimano Dura-Ace 7900 compact component group
- Lightest Giant Contact SLR composite handlebar and stem
- Highest-performance Shimano Dura-Ace Carbon C24 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
Centimeters		Degrees	Degrees	Centimeters	Centimeters	Centimeters	Centimeters	Inches
XS/43.0	385472	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5	385473	72.0	74.0	53.0	14.5	42.0	99.0	29.7
M/50.0	385474	72.5	73.0	54.5	16.5	42.0	99.0	30.6
M/L/53.5	385475	72.5	73.0	56.0	18.5	42.0	100.5	31.1
L/55.5	385476	72.5	72.0	57.5	20.5	42.0	100.8	32.0
XL/58.5	385477	72.5	72.0	59.5	22.5	42.0	102.8	32.8

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire