

# DEFY ADVANCED 3

THE MORE COMFORTABLE YOU ARE, THE MORE YOU'LL RIDE.  
THE MORE YOU RIDE, THE FASTER YOU GET. ENDURANCE  
AND SPEED, A WINNING COMBO.



## SPECIFICATIONS

FRAME COMPONENTS	SIZES	XS,S,M,M/L,L,XL
	COLORS	Composite/White/Red
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
	HANDLEBAR	Giant Connect, 31.8
	STEM	Giant Connect
	SEATPOST	Giant Vector Composite
	SADDLE	Selle Royal Seta M
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano 105 5700
	FRONT DERAILEUR	Shimano 105 5700
	REAR DERAILEUR	Shimano 105 5700
	BRAKES	Tektro TK-R540 Giant Specific, Dual Pivot
	BRAKE LEVERS	Shimano 105 5700
WHEELS	CASSETTES	Shimano 105 10-speed, [Compact] 11x28, [Triple] 12x27
	CHAIN	Shimano 105 5700
	CRANKSET	FSA Gossamer MegaExo, [Compact] 34/50, [Triple] 30/39/50
	BOTTOM BRACKET	FSA Mega-Exo, Internal Press Fit
	RIMS	Giant P-R2
	HUBS	Formula Sealed Cartridge Bearing 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Giant P-R3, 60 tpi, Flat Guard, [F] & [R] specific, 700x25
EXTRAS		

Specifications and availability subject to change without notice

## FRAME TECHNOLOGY

At the heart of this aero-sculpted beauty is an Advanced-grade composite frame with endurance-geometry for increased control and comfort. Performance features like the PowerCore bottom bracket for optimal pedaling stiffness are blended with road-smoothing features including a longer wheelbase and taller head tube. It's the best of both worlds.



## KEY UPGRADES (OVER DEFY ADVANCED 4)

- 10-speed Shimano 105 5700 shifting
- FSA Gossamer MegaExo crankset
- Selle Royal Seta M saddle

## FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
Centimeters	Compact	Triple	Degrees	Degrees	Centimeters	Centimeters	Centimeters	Centimeters	Inches
XS/43.0	385662	385762	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5	385663	385763	72.0	74.0	53.0	14.5	42.0	99.0	29.7
M/50.0	385664	385764	72.5	73.0	54.5	16.5	42.0	99.0	30.6
M/L/53.5	385665	385765	72.5	73.0	56.0	18.5	42.0	100.5	31.1
L/55.5	385666	385766	72.5	72.0	57.5	20.5	42.0	100.8	32.0
XL/58.5	385667	385767	72.5	72.0	59.5	22.5	42.0	102.8	32.8

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire