

RAPID 1

GET FIT FAST. TAKE THE SMOOTH, EFFICIENT RIDE OF A ROAD BIKE, ADD THE INCREASED CONTROL OF A FLAT HANDLEBAR. THAT'S RAPID.



SPECIFICATIONS

FRAME	
SIZES	S,M,L,XL
COLORS	Blue/White/Black
FRAME	ALUXX SL-Grade Aluminum
FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
SHOCK	N / A
COMPONENTS	
HANDLEBAR	Giant Connect, Flat 31.8
STEM	Giant Connect
SEATPOST	Giant Connect SL, Composite, 30.9
SADDLE	Selle Royal Seta M
PEDALS	Shimano M505
DRIVETRAIN	
SHIFTERS	Shimano R440
FRONT DERAILLEUR	Shimano R440
REAR DERAILLEUR	Shimano 105 5700
BRAKES	Shimano Dual Pivot, Long Reach
BRAKE LEVERS	Tektro Alloy
CASSETTES	Shimano HG-50 12x25, 9-speed
CHAIN	Shimano HG-73
CRANKSET	Shimano Tiagra, 34/50
BOTTOM BRACKET	Shimano, External
WHEELS	
RIMS	Giant P-R2
HUBS	Formula Sealed Cartridge Bearing 24/28h
SPOKES	SAPIM Race, 14/15g
TIRES	Giant P-R3, 60 tpi, Flat Guard, [F] & [R] specific, 700x25
EXTRAS	Alloy Bar Ends

FRAME TECHNOLOGY

It's versatile, it's inviting and, most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness, a stress-free commute—or both.



KEY UPGRADES (OVER RAPID 2)

- Shimano compact Tiagra crankset, Shimano M505 pedals
- Giant Connect SL composite seatpost
- Giant P-R2 rims, Formula hubs/SAPIM stainless spokes, wheelsset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
Centimeters		Degrees	Degrees	Centimeters	Centimeters	Centimeters	Centimeters	Inches
S/46.5	381073	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0	381074	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5	381075	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5	381076	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire